Serial No.: 09/902,884 Filed: July 11, 2001

Page : 2 of 13

## Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## **Listing of Claims**:

1. (Previously presented) A primary alkaline battery, comprising: a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a kerosene absorption greater than about 3.6 milliliters per gram;

an anode;

a separator; and

- 2. (Cancelled)
- 3. (Cancelled)
- 4. (Original) The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 4.0 milliliters per gram.
- 5. (Original) The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 4.5 milliliters per gram.
- 6. (Original) The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 5.0 milliliters per gram.

Serial No.: 09/902,884 Filed: July 11, 2001 Page: 3 of 13

7. (Previously presented) The battery of claim 1, wherein the carbon particles comprise between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.

- 8. (Previously presented) The battery of claim 1, wherein the carbon particles comprise between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
- 9. (Original) The battery of claim 1, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.
  - 10. (Currently amended) A primary alkaline battery, comprising: a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a BET surface area of from at least about 5 m<sup>2</sup>/g and less than to about 15 14 m<sup>2</sup>/g;

an anode;

a separator; and

- 11. (Currently amended) The battery of claim 10, wherein the expanded graphite particles have a BET surface area of from greater than about 10 m $^2$ /g to and less than about 15 14 m $^2$ /g.
  - 12. (Cancelled)

Serial No.: 09/902,884 Filed: July 11, 2001

Page : 4 of 13

13. (Cancelled)

14. (Original) The battery of claim 10, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.

- 15. (Original) The battery of claim 10, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
- 16. (Original) The battery of claim 10, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.

17-21. (Cancelled)

22. (Previously presented) A primary alkaline battery, comprising: a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a  $D_{50}$  particle size that is greater than 40 microns and less than or equal to about 100 microns;

an anode;

a separator; and

an alkaline electrolyte.

23. (Cancelled)

Serial No.: 09/902,884 Filed: July 11, 2001

Page : 5 of 13

24. (Previously presented) The battery of claim 22, wherein the expanded graphite particles have a  $D_{50}$  particle size that is greater than 40 microns and less than or equal to about 50 microns.

- 25. (Previously presented) The battery of claim 22, wherein the carbon particles comprise between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.
- 26. (Previously presented) The battery of claim 22, wherein the carbon particles comprise between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
  - 27. (Cancelled)
  - 28. (Original) A primary alkaline battery, comprising:
  - a cathode comprising

manganese dioxide and

expanded graphite particles having a kerosene absorption greater than about 4.4 milliliters per gram;

an anode;

a separator; and

- 29. (Original) The battery of claim 28, wherein the graphite particles have a kerosene absorption between about 5 and about 6 milliliters per gram.
- 30. (Original) The battery of claim 28, wherein the graphite particles have a kerosene absorption between about 5.2 and about 5.6 milliliters per gram.

Serial No.: 09/902,884 Filed: July 11, 2001

Page : 6 of 13

31. (Original) The battery of claim 28, wherein the graphite particles have a kerosene absorption about 5.4 milliliters per gram.

- 32. (Original) The battery of claim 28, wherein the cathode comprises between about 2% and about 10% of expanded graphite particles by weight.
- 33. (Original) The battery of claim 28, wherein the cathode comprises between about 3% and about 6% of expanded graphite particles by weight.
- 34. (Original) The battery of claim 28, wherein the cathode comprises between about 80% and about 95% of manganese dioxide by weight.
- 35. (Original) The battery of claim 28, wherein the cathode comprises between about 85% and about 90% of manganese dioxide by weight.
- 36. (Original) The battery of claim 28, wherein the cathode further comprises non-expanded graphite particles.
- 37. (Previously presented) The battery of claim 36, wherein the carbon particles comprise between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.
- 38. (Previously presented) The battery of claim 36, wherein the carbon particles comprise between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
  - 39. (Original) A primary alkaline battery, comprising:

Serial No.: 09/902,884 Filed: July 11, 2001

Page : 7 of 13

## a cathode comprising

manganese dioxide and

expanded graphite particles having a total pore volume greater than about 0.1 milliliter per gram;

an anode;

a separator; and

- 40. (Original) The battery of claim 39, wherein the expanded graphite particles have a total pore volume greater than about 0.15 milliliter per gram.
- 41. (Original) The battery of claim 39, wherein the expanded graphite particles have a total pore volume greater than about 0.2 milliliter per gram.
- 42. (Original) The battery of claim 39, wherein the cathode comprises between about 2% and about 10% of expanded graphite particles by weight.
- 43. (Original) The battery of claim 39, wherein the cathode comprises between about 3% and about 6% of expanded graphite particles by weight.
- 44. (Original) The battery of claim 39, wherein the cathode comprises between about 80% and about 95% of manganese dioxide by weight.
- 45. (Original) The battery of claim 39, wherein the cathode comprises between about 85% and about 90% of manganese dioxide by weight.
- 46. (Original) The battery of claim 39, wherein the cathode further comprises non-expanded graphite particles.

Serial No.: 09/902,884 Filed: July 11, 2001 Page: 8 of 13

47. (Previously presented) The battery of claim 46, wherein the carbon particles comprise between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.

- 48. (Previously presented) The battery of claim 46, wherein the carbon particles comprise between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
- 49. (Original) The battery of claim 46, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.